



GAFLAS® #75 BASE SHEET



Description

GAFLAS® #75 Base Sheet is a premium roofing base sheet constructed with a strong glass mat that is coated on both sides to ensure a closed-sheet design to prevent asphalt bleed-through. The sealed sheet also serves as an effective flame retarder for the application of torch-applied modified bitumen membranes.

Uses

GAFLAS® #75 Base Sheet is engineered for use in the construction of GAFLAS® built-up and RUBEROID® modified bitumen roofs. It is suitable for nailable specifications, such as plywood, where bleed-through is a concern.

Advantages

- Extra strength for excellent nail-holding ability. Superb tensile strength and resilience and no bleed through, thereby reducing risks of splitting and cracking of membrane.
- Will not rot, curl, or shrink; dimensionally stable for improved membrane performance.
- Designed to meet UL Class A ratings.
- Rolls out flat for easy installation.
- System guarantees are available for up to 20 years.*

Applicable Standards

Meets ASTM D4601, Type II
FM Approved
ICC ESR-1274
Miami-Dade County Product Control Approved
UL/ULC Listed

Product Specifications (nominal)

Roll Size	3 squares (320.1 gross sq. ft.) (29.7 m ²)
Roll Length	97.5' (29.7 m)
Roll Width	39.375" (1.0 m)
Approx. Roll Weight	68 lb (30.8 kg)

* See applicable guarantee for complete coverage and restrictions.